

4

3


2

1


## REVISIONS

ZONE	REV	DESCRIPTION	DATE	DRAWN BY
	A	First drawing	2020.10.15	
	B			

D



⑥

-black  
+ red


② ③

①

④ ⑤

P2

C


-black  
+ red

⑦

Lamp holder mounting dimensions drawing:

Wire parameters:

1. OD :1.3mm, PVC Insulation;
2. Conductor construction :7/0.16tinned copper;
3. Rated temperature: 80° C;
4. Rated voltage : 300V
5. wire length :30mm~2000mm.



∅8.0mm±0.05

B


E

8					
7	Lamp holder	7.8mm diameter lamp holder	pcs	1	
6	LED	F5 green yellow green short legs (3V 20ma)	pcs	1	
	LED	F5 Red hair general red short foot(2.5V 20ma)	pcs		
5	Terminal	XH2.5-T	pcs	2	
4	Housing	XH2.5-2P	pcs	1	
3	Terminal	AMP:2-487406-3	pcs	2	
2	Housing	AMP:487526-1	pcs	1	
1	Wire	UL1007#26 80°C Red;Black	pcs	1	
QC	Material	Specification	Unit	Qty	
BILL OF MATERIAL					

General Tolerance

DIMENSION  
 X.X ±0.30  
 X.XX ±0.10  
 X.XXX ±0.05

ANGLE  
 ±5°



Shenzhen Yi Da Wing technology co.,LTD

Website: <https://ydwharness.en.alibaba.com/>

Publish NO.		customer p. n.	
SHEET:	1 OF 1	part no.	
TITLE	487526-1 TO LED UL1007#26 Wire		
Approved By	Checked By	Drawn By	DATE
			2020.10.15
			SCALE
			NONE
			Units
			mm

A

A